CERASEAL

CeraSeal is a wax emulsion sealant that protects freshly cut wood and wood blanks for woodturning from cracking and dry damage. In particular, the end grain of the wood dries quickly, which can often lead to cracking. CeraSeal reduces cracking and often prevents it completely, provided the wood is of optimal quality.

PROPERTIES

- Ready to use
- Reduces end checks and drying splits by up to 95%
- Dries almost transparently
- Suitable for all varieties of hardwood and softwood
- Aids in preventing the blue stain and sap stain induced by harmful fungi
- Formulated as a non-toxic, waterbased solution
- Can be used at low temperatures



APPLICATION

Surface should be clear of dirt and debris.

Generously apply CeraSeal with a brush, roller, or sprayer until a slight drip is observed.

For logs with a diameter exceeding 60 cm, a thicker coating is needed, or alternatively, two applications should be done within a time interval a several hours. After drying the milky color of CeraSeal film turns to translucent.

CONSUMPTION

Approximately 0.3 liters of the product are required to cover 1 square meter, depending on the application technique and the type of wood.

CLEANING of TOOLS and STORAGE

Application tools should be cleaned with warm, soapy water. Unused Ceraseal should be stored in an area with a temperature above 5°C to prevent it from freezing.

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

